

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 03-041470

(43)Date of publication of application : 21.02.1991

(51)Int.Cl.

G03G 9/087

G03G 9/08

(21)Application number : 01-176863

(71)Applicant : NIPPON SYNTHETIC CHEM IND
CO LTD:THE
MITSUBISHI GAS CHEM CO INC

(22)Date of filing : 07.07.1989

(72)Inventor : MATSUMURA AKIRA
ITO TOMIJI
TAKE MORIO
KANEHARA HIDENORI

(54) TONER FOR ELECTROSTATIC IMAGE**(57)Abstract:**

PURPOSE: To form the toner which simultaneously satisfies offset resistance and fixability by specifying the ratio of acid value of a resin having a low acid value I and a resin having a high acid value II to a specific value or above and specifying $II/[I+II]$ to the value of specific range.

CONSTITUTION: The ratio of the acid value II of the resin having the higher acid value to the acid value I of the resin having the lower acid value of the resins of the toner consisting of the satd. polyester resins used for developing images as a binder resin component is specified to ≥ 1.5 . The compsn. formed by mixing and using these resins at 100 to 200° C at the ratio at which the $II/[I+II]$ attains 0.3 to 0.9 by weight and compounding of a multifunctional cyanate contg. ≥ 2 cyanate in the molecule or cyanate pre polymer and a hardening catalyst of glycidyl group-contg. acrylic resin therewith is used. The toner which simultaneously satisfies the offset resistance and fixability is produced in this way.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

Copyright © 1998,2000 Japanese Patent Office